



From Tyco Security Products

1-Button Personal Panic WS4938



Features That Make a Difference:

- Activation via one large, easy-to-use button
- Attractive, compact design
- Full two-second delay on panic button
- Integrated LED to indicate signal transmission
- Neck strap included
- Reliable 433MHz technology
- Multifunction clip included
- Water resistant
- Long-life lithium batteries included
- Supervised

For a home security system to be considered comprehensive it needs to protect individuals wherever they may be inside the home – whether they are down in the basement, cooking in the kitchen or watching television.

With DSC's wireless WS4938 single-button personal panic, users are given a portable means to call for help from anywhere in the home. The WS4938 features intuitive activation via a large, clearly defined button that incorporates a full two-second delay to help reduce false alarms. To ensure easy emergency access, the WS4938 includes a neck strap and a multifunction clip that can be mounted in a convenient location or worn on a belt.

Easy to use

The WS4938 provides users with an uncomplicated, portable means to call for help from anywhere in the home. The unit's large panic button is clearly defined to ensure trouble-free activation in times of emergency.

False Alarm Reduction

The button on the WS4938 incorporates a full two-second activation delay to help reduce false alarms and to ensure transmissions are sent to the security system only when intended.

Visual Confirmation

A red LED indicator on the WS4938 flashes to indicate that a transmission has been sent to the security system.

Value Added

The WS4938 is water resistant and includes a neck strap. Also included is a multifunction clip that allows the personal panic to be permanently mounted to a convenient location or clipped to a belt. The WS4938 uses long-life lithium batteries that are installer activated via a switch located inside the unit, a feature that helps maximize battery life. The WS4938 is compatible with all of DSC's current wireless receivers and uses reliable 433MHz wireless technology.

Supervision

The WS4938 is a supervised unit that sends periodic transmissions to the receiver to indicate functionality and battery status. If the transmission fails to reach the receiver after a programmed length of time, a trouble is indicated at the control panel keypad.

Compatibility

- PowerSeries™ Wireless Receivers
RF5132-433 / PC5132-433 / RF5108-433 / TR5164-433
- MAXSYS® Wireless Receiver PC4164-433/RF4164
- PowerSeries RFK Keypads
(RFK5500/RFK5501/RFK5516/RFK5508)
- Fixed-Message LCD Keypad with Integrated Wireless Receiver RF5501-433
- SCW9045/9047 Self-Contained Wireless Security System
- IMPASSA Self-Contained Wireless Security System
- ALEXOR Distributed Wireless Security System
- WS4920 Wireless Repeater

Specifications

Dimensions.....	2 1/4" x 1 1/4" x 7/16" (57 mm x 32 mm x 13 mm)
Weight.....	0.6 oz (18 g)
Battery	CR2025 (3V Lithium)
Operating Temperature	32° to 120°F (0° to 49°C)
Relative Humidity	5% to 93%