

# Essentials

## 2MP Varifocal IP Mini-Dome Camera



### Features That Make a Difference:

- 1080p resolution for HD images
- 2.7-12mm lens continuously monitors areas of interest
- Manage bandwidth resources with H.264 and MJPEG dual-stream encoding
- Up to 30 frames per second for seamless video streaming
- IP67 environmental rating to protect against dust and water
- IK10-rating for vandal resistance
- Power over Ethernet reduces cord build-up when running connected devices
- IR Illuminators deliver clear video when viewing dark scenes
- True Day/Night functionality for quality video recording in low light conditions
- Wide Dynamic Range to simultaneously view high-contrasting areas
- Supports corridor mode for better field of view

## Meet a Variety of Recording Requirements at a Low Cost

The Illustra Essentials Varifocal Mini-Dome cameras provide CIF to 2MP HD resolution with IR illumination to manage low light scenes. The affordable cameras capture video in a variety of lighting conditions with features such as True Day/ Night and Wide Dynamic Range. Rated IP67 for an additional degree of environmental protection, the Mini-Dome exceeds previous generations of Illustra Essentials cameras.

The Essential Varifocal Mini-Dome also features corridor mode which allows cameras to maximize video surveillance in narrow vertical situations. Ideal for hallways, retail aisles, and tunnels this mode creates a unique high quality, vertical video. Using corridor mode results in less bandwidth and storage requirements by only focusing on relevant items in the scene.

### Record Video with Low Light Clarity

Poor low-light performance by megapixel cameras hampers some of the most important tasks security professionals need to perform. Cameras that fail in low light clarity negatively impact both the necessary functions of security and cost of ownership.

The sensitive processor and sensor combination on the Essentials Varifocal Mini-Dome switches the camera automatically between color and black and white mode in a feature known as True Day/Night. Regardless of the ambient illumination level, the camera is able to maintain crystal clear images in low light scenarios.

### Balance Images with Wide Dynamic Range

The difference in extreme lighting within a scene is known as dynamic range. Cameras with the Wide Dynamic Range functionality have special software that allows them to balance foreground and background lighting for one clear image. This makes them ideal for recording areas like store entrances where the contrast between the sunshine outside and the dim lighting inside can be extremely difficult to record.

The Illustra Essentials Varifocal Mini-Dome camera takes advantage of the latest pixel-by-pixel dynamic range offered today. Maintain facial details with whole scene clarity by working within the megapixel lens to enhance the precision of the images for a high-resolution HD solution that excels in an array of challenging lighting conditions.

# Specifications

Camera	
Imager	1/2.7"
Resolution	1920 x 1080
Shutter Speed	Auto/Manual, 1/3(4)~1/100000s
Minimum Illumination	0.1 Lux/F1.4 (Color) 0 Lux/F1.4 (IR on)
S/N Ratio	> 50dB
Analog Video Output	N/A
Camera Features	
IR Illuminator	30m
Day/Night	Mechanical ICR
Backlight Compensation	Yes
Wide Dynamic Range	Yes
White Balance	Auto/Manual
Gain Control	Auto/Manual
Digital Noise Reduction	3D
Privacy Zones	Up to 4 areas
Lens	
Focal Length	2.7-12mm
Max Aperture	F1.4
Focus Control	Manual
Angle of View	H: 98° ~ 30°
Video	
Video Compression	H.264/ MJPEG
Resolutions	1080P (1920 x 1080); 1.3M (1280 x 960); 720P (1280 x 720); D1 (704 x 576/704 x 480); CIF (352 x 288/352 x 240)
Max Frame Rate	Main stream: 2MP (30ips) Sub stream: D1/CIF (30ips)
Audio	N/A
Network	
Ethernet	RJ-45 (10/100Base-T)
Wi-Fi	N/A
Supported Protocols	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter, QoS, Bonjour
ONVIF-Compliant	ONVIF, CGI
Auxiliary Interface	
Onboard Storage	N/A
Alarm Input/Output	N/A
General	
Power Supply	DC12V, PoE (802.3af)
Power Consumption	<4W
Operating Temperature	-30°C to 60°C (-22°F to 140°F)
IP Rating	IP67
Vandal Resistant	IK10
Dimensions	122mm x 89mm (4.8in x 3.5in)
Menu Languages	Chinese (simplified), English (default), French, German, Portuguese, Spanish, Italian, Dutch
Weight	0.5kg (1.1lbs)

Model	Description
IES02D1OCWIYB	Illustra Essentials 2MP Dome, 2.7-12mm, outdoor, vandal, clear, white, TDN w/IR, WDR

\*This product is subject to certain restrictions on procurement, use, funding or contracting by the United States federal government as set forth in Section 889 (Prohibition on Certain Telecommunications and Video Surveillance Services or Equipment) of the John S. McCain National Defense Authorization Act for Fiscal Year 2019.

OPTIONAL VARIFOCAL MINI-DOME ACCESSORIES					
Model	PFA137	PFB203W	PFB200C	PFA151	PFA152
Description	Junction Box	Wall Mount	In-Ceiling Mount	Corner Mount	Pole Mount
Dimensions	134mm x 134mm x 51mm (5.28in x 5.28in x 2.00in)	160mm x 120mm x 74mm (6.30in x 4.72in x 2.91in)	166mm x 78mm (6.53in x 3.07in)	243mm x 170mm x 138mm (9.60in x 6.70in x 5.43in)	117.5mm x 87mm x 21mm (4.60in x 3.40in x 0.83in)
Weight	0.6kg (1.32lbs)	0.5kg (2.20lbs)	0.32kg (.7lbs)	1.7Kg (3.75lbs)	0.2kg (0.44lbs)
Load Bearing	3kg (6.61lbs)	1kg (2.20lbs)	1kg (2.2lbs)	10Kg (22lbs)	3.0kg (6.61lbs)

ILLUSTRATION CAMERA MODEL KEY											
ILLUSTRATION	SERIES	MODEL	RESOLUTION	FORM FACTOR	LENS	ENVIRONMENT HOUSING	BUBBLE	COLOR	DAY/NIGHT/IR	WDR	OTHER
I	E = Essentials	L = Lite	01 = 1MP	B = Bullet	N = None	N = None	N = None	B = Black	C = Color Only	N = No	A = Hardware Update
	F = Flex	P = Plus	02 = 2MP	C = Compact Dome	F = Fixed	A = Indoor NonVandal	C = Clear	W = White	I = TDN w/IR	T = Multi-Exposure (>60 Frames)	1 = 2.6mm
	P = Pro	S = Standard	03 = 3MP	D = Dome	0 = 1.8–3mm	B = Outdoor NonVandal	S = Smoked		S = Soft Day/Night	Y = Yes	2 = 2.8mm
	Q = Edge		05 = 5MP	F = Fisheye	1 = 2.8–12mm	I = Indoor Vandal			T = TDN		3 = 3.7mm
			12 = 12MP	H = Micro	2 = 3–9mm	O = Outdoor Vandal					
				M = Mini-Bullet	3 = 9–22mm						
				P = PTZ	5 = 20x						
				X = Box	6 = 30x						

## Related Products



VideoEdge



exacqVision



victor

## Approvals

