

## Corrosion-Resistant Dry Chemical Hand Portable Fire Extinguishers

### Features

- Designed for corrosive environments and industrial use
- Meets or exceeds requirements of ANSI/UL 299 and 711
- DOT and USCG approved with proper bracket
- Simple operation and maintenance
- Tough, glare-resistant, one-piece mylar nameplates
- Rechargeable
- Manufactured of durable, high-quality materials
- Choice of Purple-K or ABC dry chemical agents to satisfy specific protection requirements
- Large, easy-to-read pressure gauge
- Manuals and parts lists available for training purposes
- Six-year limited warranty from date of delivery to original end-user purchaser
- Sold and serviced through an international network of independent distributors

### Application

The SENTRY Corrosion-Resistant Dry Chemical Extinguishers are designed for protection of light and ordinary hazards. These compact and portable extinguishers are suited for industrial fire protection needs especially for the corrosive environments found in the chemical industry or marine environments including:

- Warehousing
- Paint process areas
- Welding areas
- Marinas
- Seaside condominiums
- Material handling vehicles



**SENTRY 10 LB  
EXTINGUISHER**



**SENTRY 20 LB  
EXTINGUISHER**

### Description

1. The shells of SENTRY extinguishers are produced by a single-step cold deep-draw process which yields a seamless steel cylinder with an extremely high-tensile strength.
2. Unique pre-treatment of the raw low carbon steel not only consists of a cleaning process, but also applies a special lubricant which helps keep the interior and exterior shell surfaces scratch-free.
3. The collar and specially pre-formed bottom enclosure are MIG welded to produce a smooth, high-integrity weld.
4. Extinguisher shells are 100% factory hydrotested to 600 psi (41.4 bar).
5. Extinguisher shells are painted with a zinc powder primer and a powder red top coat. The powder top coat resists blistering, cracking, fading, and chipping. The powder zinc primer provides additional protection from corrosive atmospheres.
6. Before the extinguisher shells are painted, they are pre-treated using a special iron phosphate bonding process. This enhances the paint adhesion and corrosion resistance.
7. The specially formulated polyester powder paint is electrostatically applied and oven cured to help ensure complete coverage and uniform paint thickness.
8. Easy-grip stainless steel extinguisher handles are designed for maximum portability, allowing operators to fight the fire without removing work gloves.
9. Valve bodies are made from a durable extruded brass alloy which is chrome-plated for additional protection.
10. Completed valve assemblies feature brass valve stems which contain O-Ring and seat material compatible with the agent to provide reliable performance and long life.
11. Rugged all-steel pick-up tubes help provide proper and dependable agent flow through the valve body.
12. Plated brass hose ferrules are used to resist oxidation.

## Description (Continued)

13. SENTRY extinguishers have large, color-coded pressure gauges which provide a quick visual indication of unit readiness.
14. Stainless steel ring pin and chain assemblies are utilized and held in place by a visual seal to help prevent accidental discharges.
15. One piece mylar label with easy-to-read pictograms provides the user with step-by-step operating instructions and the hazard classes for which the extinguisher was designed. Label also contains useful recharge, maintenance, inspection, operating temperature, HMIS and model information.
16. Large, easy-to-scan bar coded model and UL serial numbers simplify inspection and maintenance record keeping.
17. Valve subassemblies are 100% tested for functionality before final assembly.
18. SENTRY extinguishers are vacuum-filled at the factory to precise tolerances.
19. Units are pressurized to 195 psi (13.4 bar), and 100% leak tested utilizing mass spectrometry technology.
20. Injection molded nozzle tips are designed to tight specifications and maximize the suppressing capabilities of the particular model and agent.
21. SENTRY extinguishers are shipped from the factory in individual recyclable corrugated cardboard cartons that are designed and field tested to help assure your extinguishers arrive undamaged and ready for operation. The glued one-piece cartons have carrying handles and a pressure gauge inspection port.
22. The cartons of SENTRY extinguishers are properly labeled according to the latest DOT regulations for ease of shipping in the field.
23. Dry chemical suppressing agents are manufactured from high quality raw materials and are carefully blended to meet stringent performance specifications. These agents are then tested to be free-flowing, water repellent and electrically nonconductive.
24. As a final quality control step, SENTRY extinguishers are randomly sampled for performance testing which includes weight percent discharge and discharge times.

## Agent

**ABC Suppressing Agent** – A monoammonium phosphate-based agent for use on Class A\* and Class B\*\* fires. The agent is a non-conductor of electricity for use on fires with Class C electrical conditions.

**Purple-K Suppressing Agent** – This potassium bicarbonate-based agent is the most effective dry chemical agent for knock-down of Class B\*\* fires. The agent is a non-conductor of electricity for use on fires with Class C electrical conditions.

\* Class A (wood, paper, cloth)

\*\* Class B (flammable liquids and gases)



## Ordering Information

For fire protection assistance, see your nearest Authorized SENTRY Distributor.

**Note:** The converted values in this document are provided for dimensional reference only and do not reflect an actual measurement.

SENTRY and the product names listed in this material are marks and/or registered marks. Unauthorized use is strictly prohibited.

## Specifications

SENTRY Dry Chemical Extinguishers		MODEL 10		MODEL 20	
		 003682		 003683	
<b>Model</b>		CR-AA10SI	CR-PK10SI	CR-AA20I-1	CR-PK20I
<b>Extinguisher Part No.</b>		436583	436586	434750	429012
<b>Bracket Part No.</b>		435793	435793	30937	30937
<b>Agent Capacity</b>		10 lb (4.54 kg) ABC	10 lb (4.54 kg) Purple-K	20 lb (9.07 kg) ABC	20 lb (9.07 kg) Purple-K
<b>UL Rating</b>		4-A:80-B:C	80-B:C	10-A:120-B:C	120-B:C
<b>Coast Guard Classification</b>		Type A, Size II Type B, C, Size II	Type B, C Size II	Type A, Size II Type B, C, Size II	Type B, C, Size III
<b>Discharge Time</b>		22 seconds	24 seconds	30 seconds	30 seconds
<b>Maximum Effective Range</b>		19 ft (5.8 m)	19 ft (5.8 m)	22 ft (6.7 m)	22 ft (6.7 m)
<b>Operating Temperature Range</b>		-65 °F to 120 °F (-54 °C to 49 °C)		-65 °F to 120 °F (-54 °C to 49 °C)	
<b>Agent Flow Rate</b>		0.50 lb/sec (0.23 kg/sec)	0.46 lb/sec (0.21 kg/sec)	0.75 lb/sec (0.34 kg/sec)	0.69 lb/sec (0.31 kg/sec)
<b>Charged Weight (with agent)</b>		19 lb, 4 oz (8.8 kg)	19 lb, 4 oz (8.8 kg)	33 lb (14.9 kg)	33 lb (14.9 kg)
<b>Dimensions:</b>	<b>Height</b>	20 1/2 in. (520 mm)	20 1/2 in. (520 mm)	22 1/2 in. (572 mm)	22 1/2 in. (572 mm)
	<b>Width</b>	8 1/4 in. (210 mm)	8 1/4 in. (210 mm)	9 1/2 in. (241 mm)	9 1/2 in. (241 mm)
	<b>Depth</b>	5 1/4 in. (135 mm)	5 1/4 in. (135 mm)	7 7/32 in. (183 mm)	7 7/32 in. (183 mm)
<b>Class B Fire Suppression Capability*</b>					
<b>Operator:</b>	<b>Novice</b>	80 ft <sup>2</sup> (7.4 m <sup>2</sup> )	80 ft <sup>2</sup> (7.4 m <sup>2</sup> )	120 ft <sup>2</sup> (11.15 m <sup>2</sup> )	120 ft <sup>2</sup> (11.15 m <sup>2</sup> )
	<b>Experienced</b>	200 ft <sup>2</sup> (18.58 m <sup>2</sup> )	200 ft <sup>2</sup> (18.58 m <sup>2</sup> )	300 ft <sup>2</sup> (27.87 m <sup>2</sup> )	300 ft <sup>2</sup> (27.87 m <sup>2</sup> )

\*Underwriters Laboratories classifies a "novice operator" as one who has little or no experience in operating a fire extinguisher.

Listings: UL (All Models)

Approvals: D.O.T., U.S.C.G. (All Models with proper bracket)

Operating Pressure: 195 psi (13.4 bar)

Hydrostatic Test Requirement: Once every 12 years (All Models)