



## TECHNICAL DATA SHEET

# Lifejacket Lights M3, MR3, ML3, W3, WR3 & WL3

Daniamant design and manufacture all of our products in line with the relevant worldwide approvals, technical specifications, current legislation and International directives.

Our mission is to achieve World class performance through partnerships with our suppliers, customers and employees, providing products and services that enhance the safety and security of our customers.

### Daniamant products cover 11 key areas:

- Lifejacket Lights
- Liferaft Lights
- Lifebuoy Lights
- Intrinsically Safe Lights
  - Special Lights
  - LED Flares
- Bridge Navigational Watch Alarm System (BNWAS)
  - Salinometers
  - Oil Level Alarm
  - Electronic Inclinometer
- Agency for a range of world-renowned safety product brands (supplied to the Danish market)

MODEL	M3	MR3	ML3	W3	WR3	WL3
Part number	1130	1230	1241	1330	1430	1441
Plastic Colour	Blue (Standard) others available					
Light - Output	Minimum 0.75 cd					
Light - Duration	Minimum 8 hours					
Light - Type	White Flashing LED					
Material	ABS Polycarbonate / TPE					
Storage Temperature	-30°C to + 65°C					
Operating Temperature	-1°C to + 30°C					
Storage Life	5 years					
Weight - Nominal	31,3 g	24,6 g	24,6 g	31,3 g	24,6 g	24,6 g
Battery Type	Lithium Thionyl Chloride					
Activation	Manual			Water/Manual		
Approvals - Classification Societies	SOLAS / MED / USCG					
Approvals - Country	See our web site for full list of Country approvals					

## Transport Specification

Transport Regulations are subject to change.

## Packing Specification

To minimize shipping costs, all Lifejacket Lights are packed and supplied in boxes of 250 and 500 off.

### The dimensions are:

Box of 250 off: 40 x 20 x 40 cm

Box of 500 off: 40 x 40 x 40 cm

### Approximate packed weights are:

Box of 250 off: 10 kg, including Clips 1

Box of 500 off: 20 kg, including Clips 1

