

ST-250 Signalling Torch



Daniamant design and manufacture all of our products in line with the relevant worldwide approvals, technical specifications, current legislation and International directives.

Our mission is to achieve World class performance through partnerships with our suppliers, customers and employees, providing products and services that enhance the safety and security of our customers.

Daniamant products cover 12 key areas:

· Lifejacket Lights Liferaft Lights • Lifebuoy Lights • Intrinsically Safe Lights Special Lights LED Flares • Forward Looking Sonar · Oil Level Alarm Bridge Navigational Watch Alarm System (BNWAS) Salinometers • Electronic Inclinometer · Agency for a range of world-renowned

> safety product brands (supplied to the Danish market)

MODEL	ST-250
Part Number	70-001A
Torch Plastic Colour	Yellow
Storage container plastic colour	Orange
Light - Output	250cd max.
Light - Duration	5 Hours min. (8 hours average)
Coverage	2.5 degree centre beam
Light-Type	Morse White Flashing/Constant LED
Material	Polycarbonate
Storage Temperature	-30 C to +65 C
Operating Temperature	-1 C to +30 C
Storage Life	5 years
Weight - torch including battery	78g
Weight - container, battery & spare bulb	59g
Battery Type	Alkaline
Activation	Manual
Water tightness - torch	IP67/IP68 & 50m for 1 hour
Water tightness - container	Moisture proof
Floats	Yes
Drop Test	2.5 m
Approvals - Classification Societies	SOLAS/ISO
Approvals - Country	See our website for full list of Country approvals

Transport Specification

Transport Regulations are subject to change.

Accessories

• Storage Box: 70-102 • LED Bulb: 70-103 • AA Battery: 30-119 • Torch: 70-101

Packing Specification

To minimize shipping costs all torches are packed and supplied in boxes of 10 off or 50 off.

The dimensions are:

Box of 10 off: 300 x 120 x 110 mm Box of 50 off: 300 x 300 x 300 mm

Approximate packed weights are:

Box of 10 off: 2.0 kg Box of 50 off: 7.5 kg



TECHNICAL DATA SHEET

Outline





