

# Dräger X-am<sup>®</sup> 3500 Multi-Gas Detection Device

The Dräger X-am<sup>®</sup> 3500 was especially designed for clearance measurements. The 1 to 4 gas detector reliably detects flammable gases and vapours as well as O<sub>2</sub>, CO, H<sub>2</sub>S, NO<sub>2</sub> and SO<sub>2</sub>. The innovative signalling design and extensive range of accessories ensure optimum safety and easy handling.

Switch easily between pump and diffusion mode

Slots for DrägerSensors<sup>®</sup> to measure up to four gases



Glowing green D-light (optional) indicates: tested and ready for use

Easy-to-read colour display with zoom function

Inductive charging

## Benefits

---

### **Specially designed for use with a pump, optimised for clearance measurement**

The Dräger X-am 3500 is equipped with a very powerful pump. It can be connected with hoses of up to 45 metres in length. A pump adapter makes it easy to switch between diffusion and pump mode at any time. This means the pump is only operated when you actually need it. That saves energy, reduces wear and tear, and thereby extends the lifespan of the pump.

Handy and durable, the Dräger X-am 3500 is intuitive to operate single-handedly using three function keys. The easy-to-read colour display clearly lays out all the information for you. Thanks to its compact and robust construction, the device can withstand even the harshest conditions.

---

### **Clear signalling design**

The signal system of the Dräger X-am 3500 is based on a clear colour code, in accordance with the requirements of the EN 60079-29-1, EN 45544-1 and EN 50104:

- Red light = gas alarm
- Yellow light = device-related alarm, e.g. low battery
- Green light = device is ready for use

The green glow of the D-light allows you to see from a distance whether the device has been properly tested and is ready for use.

In case of an alarm, the X-am 3500 alerts you with colourful alarm LEDs, a loud horn (100 dB(A) at a distance of 30 cm), and clearly palpable vibration. Optionally, four preset hazard symbols are available for the display which explicitly indicate the presence of explosive or toxic gas hazards, for example. This allows the user to easily recognise the type of hazard based purely on the symbol displayed.

---

### **Economical Fleet Management**

Bumptest and calibration are carried out simply and quickly using the Dräger X-dock® calibrating station. Its low test gas consumption keeps operating costs to a minimum.

Its reporting function and numerous other useful features make the X-dock Manager PC software a smart addition to any fleet management operation. To identify the devices in the fleet, you can either use tried and tested barcodes or an integrated RFID transponder.

---

### **Inductive charging protects against wear and tear**

The X-am 3500 features inductive charging. This makes it easier to operate and increases the lifespan of the device. Issues like corrosion and contact problems in the charging cradle are a thing of the past. You can charge (outside of explosion-hazard zones) and measure at once, e.g. when in use inside vehicles or on machinery. The charging cradle can connect with one another, taking up minimal space, and are compatible with existing Dräger X-am® series cradles.

## Details



D1-4324-2017

Pump adapter



D-6555-2017

Protective rubber boot



D-27/812-2017

Dräger X-dock® module

## Comparison of Dräger X-am® 3500 and Dräger X-am® 8000

Features	Dräger X-am® 3500	Dräger X-am® 8000
Number of measuring gases	1 to 4	1 to 7
Internal pump, activation with pump adapter	Yes	Yes, optional
Inductive charging	Yes	Yes
Customer-specific settings when ordering	No	Yes
Shoulder strap included as standard	No	Yes
Catalytic bead sensor DrägerSensor® CatEx 125 PR	Yes	Yes, configurable
Electrochemical (EC) DrägerSensors®: XXS O <sub>2</sub> , XXS CO LC, XXS H <sub>2</sub> S LC, XXS NO <sub>2</sub> , XXS SO <sub>2</sub>	Yes	Yes, configurable
Electrochemical (EC) DrägerSensors®: other sensors/special gases	No	Yes, configurable
Infrared (IR) DrägerSensors® Dual IR Ex/CO <sub>2</sub> , IR-Ex, IR-CO <sub>2</sub>	No	Yes, configurable
Photoionisation detector (PID) DrägerSensors®: PID HC, PID LC ppb	No	Yes, configurable
Automatic measurement range switching for the catalytic bead sensor, catalytic bead sensor, measuring gas: methane	No	Yes, configurable
Assistant: Confined Space, Leak Search, Benzene/Pre-Tube	No	Yes, only when a pump is installed
Event report (incl. impact detection)	No	Yes, configurable
Bluetooth® <sup>1</sup>	No	Option

<sup>1</sup> Bluetooth® is a registered trademark of Bluetooth SIG, Inc.

Dräger offers two different multi-gas detection devices with internal pump: Dräger X-am® 8000 and Dräger X-am® 3500. The different features of both devices are summarised in the table above.

## Accessories



D-6562-2017

### Inductive charger

To charge the device inductively



D-6545-2017

### Pedestal

To stand the device upright for area monitoring. The pedestal can be used with or without a shoulder strap.



D-6555-2017

### Protective rubber boot

Prevents damage and wear in harsh environments. The protective boot can easily be replaced by the user.




D-6547-2017

### Shoulder strap with adhesive label


With the shoulder strap you can comfortably carry the device. The corresponding adhesive label can be marked individually with device specific information, e.g. sensor assortment.

# Services



## Product Service

Our product service department supports you with a range of service packages – in our shops or on site in your plant. Care, servicing and maintenance are key factors when it comes to safety. Diligent maintenance and care is also absolutely necessary from an economics perspective. Preventive checks, service procedures and original replacement parts make your investment last longer.



## Rental Service

From bridging a temporary shortage of equipment to procuring special equipment for applications involving specific requirements: If you only need to cover a temporary higher demand, then Dräger Rental Service with over 65,000 pieces of rental equipment is an economical alternative to purchasing. Fast, straightforward and with a wide range of additional services available upon request.



## Training

The Dräger Academy has imparted well-founded and practical knowledge for over 40 years. With over 110 authorized trainers and more than 600 available topics, we conduct more than 2,400 training sessions per year. We equip your employees with the knowledge required for real-life situations and ensure that the learned material can be recalled and applied reliably – in their everyday work and especially in stressful situations. To meet your needs, we are also happy to develop a customized training program specifically for you.



## On-site Safety Service

Whether through a rental shop, personnel services or comprehensive safety management, our On-Site Safety Services provide support in all projects where there are particular safety risks – not to mention normal day-to-day business.

## Technical Data

Dimensions (H x W x D)	179 x 77 x 42 mm	
Weight	Approx. 495 g, depending on sensor configuration, without strap, without pump Approx. 550 g, depending on sensor configuration, without strap, with pump	
Housing	Durable two-component housing	
Display	High-contrast colour display	
Temperature	-20 °C to +50 °C	
Pressure	700 to 1.300 hPa	
Relative humidity	10 to 90% (short-term up to 95%) r.h.	
Alarms	Visual	3 LED 'red' (gas alarms), 3 LED 'yellow' (device alarms)
	Acoustic	Multi-tone, typically 100 dB(A) at 30 cm
	Vibration	
Ingress protection class	IP 67	
Energy supply	Lithium-ion battery, rechargeable, inductive charging	
Operating times (Diffusion)	With CatEx and 3 EC sensors	Typically 24 hours
	With 3 EC-sensors	Typically 120 hours
Charging times	Typically 4 hours after use during a shift of max. 10 hours	
Start-up times	Typically <60 seconds for standard sensors	
Data storage	12 MB, e.g. at 10 minutes per hour of gas exposure with measuring values changing by the second on all 4 channels: approx. 300 hours	
Pump operation	Max. hose length 45 m	
Approvals	ATEX / IECEx	I M1, II 1G Ex da ia I Ma, Ex da ia IIC T4 Ga Metrological approval pending
	EAC (Please contact Dräger regarding availability.)	PO Ex da ia I Ma X Ex da ia IIC T4 Ga X
	cCSAus (Please contact Dräger regarding availability.)	Class I, Zone 0, AEx da ia IIC T4 Ga Div 1, Gr. E, F, G T4 C22.2 No. 152, ANSI-ISA 12.13.01:2000
	CE labelling	
	MED / DNV GL (Please contact Dräger regarding availability.)	
Manufacturer's warranty	3 years for the device 1 year for the power supply Sensors: see DrägerSensor® & Portable Instruments Handbook	

## Ordering Information

Dräger X-am® 3500	Order No.
consists of: device with power supply (Lithium-ion battery), integrated pump, pump adapter, data logger, manufacturer's certificate, certificate of calibration. Ex = CatEx 125 PR, Calibration gas = Methane. Instruction for use included as standard in the following languages: DE, EN, FR, ES, PT, IT, NL, RU, ZH, JA	
Dräger X-am® 3500 Ex, O <sub>2</sub> <sup>1</sup> (without charging equipment)	83 28 412
Dräger X-am® 3500 Ex, O <sub>2</sub> , H <sub>2</sub> S LC <sup>1</sup> (without charging equipment)	83 28 414
Dräger X-am® 3500 Ex, O <sub>2</sub> , CO LC <sup>1</sup> (without charging equipment)	83 28 416

## Ordering Information

Dräger X-am® 3500 Ex, O <sub>2</sub> , CO LC, H <sub>2</sub> S LC <sup>1</sup> (without charging equipment)	83 28 418
Dräger X-am® 3500 Ex, O <sub>2</sub> , CO LC, H <sub>2</sub> S LC <sup>1</sup> Set (with charging equipment)	83 28 419
Dräger X-am® 3500 Ex, O <sub>2</sub> , CO LC <sup>1</sup> , NO <sub>2</sub> (without charging equipment)	83 28 422
Dräger X-am® 3500 Ex, O <sub>2</sub> , H <sub>2</sub> S LC <sup>1</sup> , SO <sub>2</sub> (without charging equipment)	83 28 424
Instruction for use on request, also available in the following languages (please indicate when ordering): DA, FI, NO, SV, PL, HR, SL, SK, CS, BG, RO, HU, EL, TR, KO	90 33 668
Technical handbook available in the following languages: DE, EN, FR, ES, RU	Available to download from the product website.

Sensors	Measuring Range	Resolution	Order No.
CatEx 125 PR <sup>1</sup>	0–100 % UEG	1 % UEG	68 12 950
DrägerSensor® XXS O <sub>2</sub> <sup>1</sup>	0–25 vol%	0.1 vol%	68 10 881
DrägerSensor® XXS CO LC <sup>1</sup>	0–2,000 ppm	1 ppm	68 13 210
DrägerSensor® XXS H <sub>2</sub> S LC <sup>1</sup>	0–100 ppm	0.1 ppm	68 11 525
DrägerSensor® XXS NO <sub>2</sub>	0–50 ppm	0.1 ppm	68 10 884
DrägerSensor® XXS SO <sub>2</sub>	0–100 ppm	0.1 ppm	68 10 885

<sup>1</sup> A three-year manufacturer's warranty applies to these sensors. Legal rights accruing from defects remain unaffected.

### Power supply unit

Energy supply (incl. back housing)	(included as standard)	83 26 817
------------------------------------	------------------------	-----------

### Charging accessories

Inductive charger for charging 1 device		83 25 825
Adapter for power plug		83 25 736
Power plug for charging 1 device		83 16 997
Power plug for charging 5 devices		83 16 994
Power plug 100–240 VAC; 1.33 A, for charging up to 5 devices	(requires adapter 83 25 736)	83 21 849
Power plug 100-240 VAC; 1.33 A, for charging up to 20 devices	(requires adapter 83 25 736)	83 21 850
Vehicle connector cable 12/24 V for charging 1 device		45 30 057
Vehicle connector cable 12/24 V DC for charging up to 5 devices	(requires adapter 83 25 736)	83 21 855
Vehicle mount	(requires adapter for power plug 83 25 736 and vehicle connector cable 12/24 V DC 83 21 855)	83 27 636

### Pump accessories

Dust and water filter for pump inlet	(included in device when pump option is selected)	83 19 364
Pump adapter	(included in device when pump option is selected)	83 26 820

### Probes and Hoses

Telescopic probe 100	Connection for filter is included in order no. 83 19 364 (Dust/Water Filter).	83 16 530
----------------------	---	-----------

## Ordering Information

Telescopic probe 150, stainless steel	Connection for filter is included in order no. 83 19 364 (Dust/Water Filter).	83 16 533
5 m FKM hose, 3.2 mm, with adapters		83 25 705
10 m FKM hose, 3.2 mm, with adapters		83 25 706
20 m FKM hose, 3.2 mm, with adapters		83 25 707
45 m FKM hose, 3.2 mm, with adapters		83 28 212
Float probe EPP, incl. 3 m hose, 3.2 mm		83 25 831
Float probe EPP, incl. 10 m hose, 3.2 mm		83 25 832
Float probe (transparent), with adapter		83 27 654
Additional probes, hoses and accessories are available from Dräger. Please contact us.		
<b>Calibration accessories</b>		
Dräger X-am® 3500/8000 calibration adapter		83 26 821
Dräger X-dock® Module Dräger X-am® 8000	(can also be used with X-am® 3500)	83 21 893
Dräger X-dock® Module Dräger X-am® 8000+ charging	(can also be used with X-am® 3500)	83 21 894
Dräger X-dock® 5300 (Dräger X-am® 8000) with Master	(can also be used with X-am® 3500)	83 21 882
Nonane Tester		83 25 861
Test gases		Please contact Dräger.
<b>Accessories for measured value acquisition and configuration</b>		
Dräger CC-Vision		Freeware ( <a href="http://www.draeger.com/software">www.draeger.com/software</a> )
Dräger GasVision License Key		83 25 646
USB Dira Dongle / IR interface		83 17 409
Holder for USB Dira Dongle		83 25 859
<b>Other accessories</b>		
Protective rubber boot, removable		83 25 858
Leather case for the device		83 27 664
Transport case (empty)		83 27 661
Protective Display cover (set of three)		83 26 828
Shoulder strap (complete)	(requires bow for shoulder strap – 83 26 819)	83 26 823
Retractable lanyard	(requires connector for shoulder strap)	83 23 032
Holder for labels (on strap)		83 26 824
Adhesive labels for individual inscriptions, for holder on strap, silver (set of 5)		83 27 645
Pedestal for holding device upright, e.g. for area monitoring	(requires connector for shoulder strap)	83 25 874
Transponder reader for reading the integrated RFID transponder (optional)		65 59 283